



TILLMAN®

584-60 | 18 oz. White Fiberglass Welding Curtain, No Coating

SPECIFICATION SHEET

Description

Tillman welding curtains are essential safety items for work spaces in which welding, torching, brazing or plasma cutting takes place.

The Tillman 584 welding curtain is an economical option as a welding curtain as it is able to withstand temperatures up to 1000° F and used for light duty applications.

The 584 offers excellent protection from both vertical splatter and sparks while maintaining its fabric strength.

Features

- 18 oz. White Fiberglass, plain weave.
- Heat treated woven uncoated fiberglass
- Temperature rating 1,000°F (550°C)
- Fire Retardant qualities used for welding
- Protects against sparks on vertical plane
- Sizes: 40" or 60" wide, 50 yard rolls, 6'x6', 6'x8', 10'x10', custom blankets.

Approved Welding Curtain



Performance Data

FM Approved - 4950
Europe BSEN 476 Part 7
European Union CE

Technical Specifications

Blanket Material:	Fiberglass - WARP-ET9 430Tex / WEFT ET9 430 Tex
Coating Material:	None, Uncoated
Thread Count:	WARP 8 / WEFT 5.7
Thickness:	.075 mm
Weight:	18 oz
Tensile Strength:	Warp: 350 lbs./inch (62.5 kg/cm) WARP 1200 / WEFT 800

Applications

- Construction sites
- Wind energy
- Fabrication
- Steel Mills
- Oil & Gas refineries
- Farming & Agriculture
- Shipyards
- Railway and metro workers
- Industrial facilities
- Manufacturing
- Pipe fabrication



TILLMAN®