Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY *(As Used on Label and List)* *Tillman 591*	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name IMG	Emergency Telephone Number 310-764-0110
Address *(Number, Street, City, State, and ZIP Code)*	Telephone Number for information 310-764-0110
1300 W. Artesia Blvd.	Date prepared April 19, 2012
Compton, CA 90220	Signature of Preparer *(optional)*

Section II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	%*(optional)*
Fibrous Glass	10 mg/m3 of air			
	For fiber diameters			
	Less than 7 micron.			

Section III - Physical/Chemical Characteristics

Boiling Point	N/A	Specific Gravity (H_2O = 1)	1.8
Vapor Pressure (mm Hg)	N/A	Melting Point	>1000F.
Vapor Density (AIR = 1)	N/A	Evaporation Rate (Butyl Acetate = 1)	N/A
Solubility in Water Negligible			
Appearance and Odor Yellow fabric with a yellow coating on one side/no odor.			

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used) >250 C	Flammable Limits	LEL N/A	UEL N/A
Extinguishing Media : Water, carbon dioxide, dry chemical			
Special Fire Fighting Procedures None Known			
Unusual Fire Explosion Hazards : None Known			
Flammable Limits: LEL: N/A UEL: N/A			

(Reproduce locally) OSHA 174, Sept. 1985

Section V - Reactivity Data

Stability	Unstable		Conditions to Avoid :None Known
	Stable	X	

Incompatibility *(Materials to Avoid): Strong oxidizing agents.*			
Hazardous Decomposition or By products: Carbon dioxide, carbon monoxide, hydrogen chloride			
Hazardous Polymerization	May Occur		Conditions to Avoid: None Known
	Will Not Occur	X	

Section VI - Health Hazard Data

Route(s) of Entry: This material can enter the body through inhalation of nuisance dust.	Inhalation?	Skin?	Ingestion?
Health Hazards *(Acute and Chronic)* Raspy , sore throat, redness and itching of skin and eyes.			
Carcinogenicity: This material is not known to be a carcinogen.	NTP?	IARC Monographs?	OSHA Regulated?
Signs and Symptoms of Exposure: Sore throat, itching of skin or eyes.			
Medical Conditions Generally Aggravated by Exposure:Respiratory ailments			
Emergency and First Aid Procedures : for skin-wash with soap and warm water. For eyes,flush with cool water. For throat: remove person to fresh air. If any of these conditions persist, seek medical attention.			

Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled : Material is a solid.
Waste Disposal Method: Burial in a federal, state or locally approved landfill.
Precautions to Be taken in Handling and Storing:Use adequate material handling equipment.
Other Precautions : None known

Section VIII - Control Measures

Respiratory Protection *(Specify Type)* use a dust mask when cutting.		
Ventilation	Local Exhaust None Needed	Special None Needed
	Mechanical *(General None Needed*	Other: None Needed

Protective Gloves Cotton gloves	Eye Protection As a matter of course.
Other Protective Clothing or Equipment Wear long sleeve garments	
Work/Hygienic Practices Wash with soap and water after handling	

* U.S.G.P.O.: 1986 - 491 - 529/45775