



TILLMAN®

948



CUT RESISTANCE GLOVES

Light Cut Hazard with Durable Abrasion Protection



The 948 offers excellent light duty ANSI A2 Cut resistance and EN 388 level 4 Abrasion in an ultrathin and breathable 18-gauge seamless glove.

FEATURES

- Ultrathin 18-gauge HPPE shell is lightweight and comfortable for all day wearing.
- 4-way stretch HPPE weave hugs the hand for a perfect fit.
- Nitrile micro-foam coating disburbs oils, grease or fluids away for excellent gripping power.
- Outstanding fingertip sensitivity for working with the smallest of parts.
- EN 388 Level 4 abrasion resistance for longer wear time and a longer glove life.
- Seamless construction offers excellent dexterity and sense of touch.
- Able to withstand multiple launderings for longer life.
- Sizes Available: S, M, L, XL, 2X.

APPLICATIONS

General duty, Material handling, Manufacturing, Assembly line production, Final assembly, Parts handling, Automotive assembly, Carpentry, Construction, HVAC, Shipping & Receiving activities



PERFORMANCE DATA:



EN 388: 4341

- Abrasion Resistance - 4
- Cut Resistance - 3
- Tear Resistance - 4
- Puncture Resistance - 1




ANSI 105 (2016)

- Cut Resistance - A2

- 1 Super soft glass fiber blend liner.
- 2 Comfortable & breathable shell for all day wear.
- 3 Nitrile micro-foam coating resists tears extending the glove life.
- 4 Fine movement with excellent dexterity and tactility.
- 5 Colored cuff for easy size indication.

PACKAGING INFORMATION

- Each pair is individually packaged on a header card
 - Minimum Order Quantity: 6 pairs per size
 - Case Quantity: 72 pairs per size



TILLMAN®