



TILLMAN®

952



CUT RESISTANCE GLOVES

Moderate Cut Hazard & High Abrasion Risk in a Versatile Glove



Increase worker confidence with the versatile and breathable 13-gauge 952. The seamless design offers ANSI A4, ISO D, cut resistance for moderate duty cut and EN 388 4 abrasion resistance.

FEATURES



- Proprietary HPPE blend provides excellent cut, ANSI A4, and abrasion, EN388 5, resistance for longer wear time and longer glove life.
- Strong 13-gauge HPPE shell is lightweight and comfortable for all day wearing.
- 4-way stretch HPPE weave hugs the hand for a perfect fit.
- Seamless construction offers excellent dexterity and sense of touch.
- High vis color for easy hand visibility and compliance detection.
- Smooth nitrile coating provides a superior grip and won't slip when trying to get a hold on wet or dry surfaces.
- Sizes Available: S, M, L, XL.

APPLICATIONS

Metallurgy, General Duty, Material Handling, Manufacturing, Sheet Metal Handling, Assembly Line Production, Parts Handling, Automotive Assembly, Carpentry, Construction, Glass Handling, Hvac, Roofing




PERFORMANCE DATA:

 <p>EN 388: 4544</p> <ul style="list-style-type: none"> • Abrasion Resistance - 4 • Cut Resistance - 5 • Tear Resistance - 4 • Puncture Resistance - 4 	 <p>ANSI 105 (2016)</p> <ul style="list-style-type: none"> • Cut Resistance - A4
---	--

PACKAGING INFORMATION

- Each pair is individually packaged on a header card
 - Minimum Order Quantity: 6 pairs per size
 - Case Quantity: 72 pairs per size

- 1 Super soft glass fiber blend liner.
- 2 Comfortable & breathable shell for all day wear.
- 3 Smooth nitrile coating provides a great grip and resists tears.
- 4 Able to withstand multiple launderings for longer life.
- 5 Great dexterity and tactical feel.
- 6 Colored cuff for easy size indication.



TILLMAN®