

CERTIFICATE OF COMPLIANCE

Certificate Number 120514-MH28336
Report Reference MH28336-20120228
Issue Date 2014-December-05
Issued to: Westex Inc.
2845 W. 48th PL.
Chicago, IL 60632


This is to certify that representative samples of Component-Industrial Flash Fire
Refer to the attached tables for Style Designations

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

Standard(s) for Safety: NFPA 2112, Standard on Flame-Resistant Garments for Protection of Industrial Personnel Against Flash Fire, 2012 Edition

Additional Information: See the UL Online Certifications Directory at www.ul.com/database for additional information

Only those products bearing the UL Recognized Component Mark should be considered as being covered by UL's Recognition and Follow-Up Service.

The UL Recognized Component Mark generally consists of the manufacturer's identification and catalog number, model number or other product designation as specified under "Marking" for the particular Recognition as published in the appropriate UL Directory. As a supplementary means of identifying products that have been produced under UL's Component Recognition Program, UL's Recognized Component Mark: , may be used in conjunction with the required Recognized Marks. The Recognized Component Mark is required when specified in the UL Directory preceding the recognitions or under "Markings" for the individual recognitions.

The final acceptance of the component is dependent upon its installation and use in complete equipment submitted to UL LLC.

Look for the UL Recognized Component Mark on the product.

William R. Carney, Director, North American Certification Programs

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at www.ul.com/contactus



CERTIFICATE OF COMPLIANCE

Certificate Number 120514-MH28336
Report Reference MH28336-20120228
Issue Date 2014-December-05

The following outer shell fabrics may be produced in any color:

Style Designation	Weight (oz/yd ²)		Material Composition	Weave	Finish
	Un-Finished	Finished			
128 TrueComfort™	5.0	5.5	100% Cotton	Interlock Knit	TrueComfort Flame Retardant
180 UltraSoft® Fleece	9.4	11.0	88% Cotton/12% Nylon	Fleece Knit	Ultra Soft Flame Retardant
301 UltraSoft® Twill	5.7	7.0	88% Cotton/12% Nylon	Twill	Ultra Soft Flame Retardant
306 Indura® Denim	10.0	12.0	100% Cotton	Twill	INDURA Flame Retardant
391 UltraSoft® Denim	11.0	13.0	88% Cotton/12% Nylon	Twill	Ultra Soft Flame Retardant
451 UltraSoft® Twill	7.5	9.0	88% Cotton/12% Nylon	Twill	Ultra Soft Flame Retardant
881, Ultrasoft® Duck	7.0	8.5	88% Cotton/12% Nylon	Basket	Ultra Soft Flame Retardant
961 UltraSoft® Rough House Duck	8.5	11.0	88% Cotton/12% Nylon	Duck	Ultra Soft Flame Retardant
20 Indura® Twill	5.5	7.0	100% Cotton	Twill	INDURA Flame Retardant
30 Indura® Twill	5.4	7.0	100% Cotton	Twill	INDURA Flame Retardant
45 Indura® Twill	7.5	9.0	100% Cotton	Twill	INDURA Flame Retardant
85 Indura® Sateen	7.5	9.0	100% Cotton	Sateen	INDURA Flame Retardant
308 Indura® Denim	10.8	14.0	100% Cotton	Twill	INDURA Flame Retardant
901 UltraSoft AC® Twill	5.4	7.0	88% Cotton/12% Nylon	Twill	Ultra Soft AC Finish
951 Ultra Soft AC Twill	7.5	9.0	88% Cotton/12% Nylon	Twill	Ultra Soft AC Finish

William R. Carney, Director, North American Certification Programs

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at www.ul.com/contactus



CERTIFICATE OF COMPLIANCE

Certificate Number 120514-MH28336
Report Reference MH28336-20120228
Issue Date 2014-December-05

The following pocketing fabrics may be produced in any color:

Style Designation	Weight (oz/yd ²)	Material Composition	Weave	Finish
37 INDURA	6.8	100% Cotton	Plain	INDURA Flame Retardant

The following Rib Knit fabric may be produced in any color:

Style Designation	Weight (oz/yd ²)	Material Composition	Weave	Finish
129 TrueComfort™	6.0	97% cotton / 3% spandex	Rib Knit	TrueComfort Flame Retardant Finish
181, Ultrasoft® Rib Knit	10.0	86% Cotton/12% Nylon/2% Spandex	Rib Knit	Ultrasoft FR finish

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

William R. Carney, Director, North American Certification Programs
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at www.ul.com/contactus

