

TILLMAN 1477 CUT RESISTANT TRUEFIT™ GLOVES

TrueFit Glove with ANSI A7 Cut Resistance.
The protection you need from the name you trust



Table of Contents

Click on the headers below (they are linked to the pages within the document):

- [Marketing Bulletin](#)
- [Pricing Bulletin](#)
- [1477 Sell Sheet](#)
- [1477 Specification Sheet](#)
- [Declaration of Conformity](#)
- [Click here for the 1477 website page](#)



MARKETING BULLETIN

TILLMAN 1477 CUT RESISTANT TRUEFIT™ GLOVES

TrueFit™ Gloves with ANSI A7 Cut Resistance
The protection you need from the name you trust


Overview

Introducing the Tillman 1477, a version of Tillman's bestselling TrueFit glove with a Para-Aramid lining, achieving ANSI A7 cut resistance.

Handling and work gloves need to protect your hands while providing the everyday comfort and durability you demand. Enter the Tillman 1477 TrueFit glove with ANSI A7 cut resistance, and Level 4 Abrasion and Puncture resistance. The 1477 defines quality, accentuates comfort, and delivers the protection you need.

1477 Features


- ANSI A7 cut resistance is achieved with a Para-Aramid lining for unbeatable cut resistance, dexterity and comfort.
- Para-Aramid lining on the fingers, palm and back of hand for complete protection.
- Level 4 Puncture and Level 4 Abrasion ratings.
- Offers that great TrueFit feel you expect from Tillman.
- High-Vis color keeps hands seen and safe.
- Soft, abrasion resistant Goatskin.
- Rough side out double palm for longer life and better gripping power.
- Reinforced thumb to protect severe stress areas.
- Top grain leather side bolsters add additional protection for side surface work.
- An elastic cuff with a Thermoplastic Rubber (TPR) and hook and loop closure provides a secure fit.
- Breathable form fitting spandex back keeps hands cool and provides a precision fit.
- All fingertips covered in leather for heavy wear area protection and double stitched for extra strength.
- Smooth surface fingers for improved handling.
- Offered in sizes S, M, L, XL, 2X, 3X.



Compliance

The Tillman 1477 glove complies with the American National Standard for Hand Protection, ANSI ISEA 105-2016.

DuPont™ and Kevlar® are trademarks or registered trademarks of E.I. du Pont de Nemours and Company.



MARKETING BULLETIN

TILLMAN 1477 CUT RESISTANT TRUEFIT™ GLOVES

TrueFit Gloves with ANSI A7 Cut Resistance

Applications

- Construction sites
- Wind energy
- Demolition and salvage
- Airports
- Fabrication
- Road construction
- Farming and agriculture
- Utility crews
- Shipyards
- Railway and metro workers



Availability

- Sizes **S**, **M**, **L**, **XL**, **2X**, and **3X** are in stock, ready for orders.

Product Replacement

The **1477** replaces the **1470K** TrueFit™ gloves. With the launch of the **1477**, the **1470K** will be available until quantities are depleted.

Packaging Information

- Each pair is individually carded and 12 or 6 pairs are packaged in a poly bag.
 - Minimum Order Quantities:
S, M, L, XL – 12 pair per size.
2X and 3X – 6 pair per size.
- Case Quantity: 72 pairs per size.

Product Information

All information relevant to this product can be found at www.jtillman.com.

Model Numbers & Sizes

Part Numbers	Size	Color
1477S	Small	Tillman 1477 TrueFit Glove with ANSI A7 Cut Resistance. High- Vis Yellow and Pearl Goatskin.
1477M	Medium	
1477L	Large	
1477XL	XL	
14772X	2X	
14773X	3X	


Ordering

For ordering information, please contact John Tillman Customer Service at 800.255.5480. Standard terms apply when ordering.

California Proposition 65

Part Numbers	Exposure to	Type of Toxicity
1477S, 1477M, 1477L, 1477XL, 14772X, 14773X	This product can expose you to chemicals including DEHP or Di(2-ethylhexyl) phthalate.	Cancer, Developmental, Male & Female

 **WARNING:** This product can expose you to chemicals including DEHP or Di(2-ethylhexyl) phthalate, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.p65warnings.ca.gov.



PRICING BULLETIN

TILLMAN 1477 CUT RESISTANT TRUEFIT™ GLOVES

TrueFit Gloves with ANSI A7 Cut Resistance

The Tillman 1477, a version of Tillman's bestselling TrueFit glove with a Para-Aramid lining, achieving ANSI A7 cut resistance.

1477 Features

- ANSI A7 cut resistance is achieved with a Para-Aramid lining for unbeatable cut resistance, dexterity and comfort.
- Para-Aramid lining on the fingers, palm and back of hand for complete protection.
- Level 4 Puncture and Level 4 Abrasion ratings.
- Offers that great TrueFit feel you expect from Tillman.
- High-Vis color keeps hands seen and safe.
- Soft, abrasion resistant Goatskin.
- Rough side out double palm for longer life and better gripping power.
- Reinforced thumb to protect severe stress areas.
- An elastic cuff with a Thermoplastic Rubber (TPR) and hook and loop closure provides a secure fit.
- Breathable form fitting spandex back keeps hands cool and provides a precision fit.
- Double stitching on forefinger provides extra strength.
- Offered in sizes S, M, L, XL, 2X, 3X.



Product Replacement


The **1477** replaces the **1470K** TrueFit™ gloves. With the launch of the **1477**, the **1470K** will be available until quantities are depleted.


PART NUMBER	DESCRIPTION	SIZE	UPC	STOCK STATUS	UNIT OF MEASURE	MINIMUM ORDER QTY.	LIST PRICE	DISTRIBUTOR NET
1477S	TRUEFIT™ Gloves with ANSI A7 Cut Resistance, Level 4 Puncture and Level 4 Abrasion protection. High-Vis Yellow and Pearl Goatskin.	Small	608134147723	Available	1 Pair	12	\$23.00	\$13.80
1477M		Medium	608134147716	Available	1 Pair	12	\$23.00	\$13.80
1477L		Large	608134147709	Available	1 Pair	12	\$23.00	\$13.80
1477XL		X-Large	608134147747	Available	1 Pair	12	\$23.00	\$13.80
14772X		2X Large	608134147754	Available	1 Pair	6	\$23.00	\$13.80
14772X		3X Large	608134147761	Available	1 Pair	6	\$23.00	\$13.80

WARNING

Gloves are cut-resistant, not cut proof. Extreme caution should be used when handling sharp objects and around machinery. Read, understand and follow all labels and instructions prior to use. Inspect gloves before each use and remove from service if there is any evidence of damage or excessive wear.

DuPont™ and Kevlar® are trademarks or registered trademarks of E.I. du Pont de Nemours and Company.

 WARNING: This product can expose you to chemicals including DEHP or Di(2-ethylhexyl) phthalate, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.p65warnings.ca.gov.





TILLMAN®

1477

A7 CUT RESISTANT TRUEFIT™ GLOVES

An excellent, all-purpose TRUEFIT™ glove with ANSI A7 Cut Resistance.



Keep hands seen and protected against abrasions and lacerations when working with sharp tools and sharp materials with the Tillman 1477.

FEATURES


- ANSI A7 cut resistance is achieved with a Para-Aramid lining for unbeatable cut resistance, dexterity and comfort.
- Para-Aramid lining on the fingers, palm and back of hand for complete protection.
- Level 4 Puncture and Level 4 Abrasion ratings.
- Offers that great TrueFit feel you expect from Tillman.
- High-Vis color keeps hands seen and safe.
- Soft, abrasion resistant Goatskin.
- An elastic cuff with a Thermoplastic Rubber (TPR) and hook and loop closure provides a secure fit.
- Breathable form fitting spandex back keeps hands cool and provides a precision fit.
- Double stitching on forefinger provides extra strength.
- Offered in sizes S, M, L, XL, 2X, 3X.

PACKAGING INFORMATION

- Each pair is individually carded and 12 or 6 pairs are packaged in a poly bag.
 - Minimum Order Quantities:
 - S, M, L, XL** – 12 pair per size
 - 2X and 3X** – 6 pair per size
- ° Case Quantity: 72 pairs per size


WARNING

Gloves are cut-resistant, not cut proof. Extreme caution should be used when handling sharp objects and around machinery. Read, understand and follow all labels and instructions prior to use. Inspect gloves before each use and remove from service if there is any evidence of damage or excessive wear.

 WARNING: This product can expose you to chemicals including DEHP or Di(2-ethylhexyl) phthalate, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.p65warnings.ca.gov.



- 1** A7 cut resistance and comfort – palm, back of hand and fingers.
- 2** Rough side out double palm for longer life and better gripping power.
- 3** Reinforced thumb to protect severe stress areas.
- 4** Smooth surface fingers for improved handling.
- 5** Elastic cuff with hook and loop closure provides secure fit, less bulk.
- 6** Top grain leather side bolsters add additional protection for side surface work.
- 7** All fingertips covered in leather for heavy wear area protection.



TILLMAN®

The Brand Pros Demand



TILLMAN®

1477 TrueFit™ Goatskin Gloves With ANSI A& Cut Resistance

SPECIFICATION SHEET

Description

Handling and work gloves need to protect your hands while providing the everyday comfort and durability you demand.

With the Tillman 1477 hands are seen and protected against abrasions and lacerations when working with sharp tools and sharp materials.

The Tillman 1477 TrueFit glove the protection hard working hands require with ANSI A7 cut resistance, and Level 4 Abrasion and Puncture resistance. The 1477 defines quality, accentuates comfort, and delivers the protection you need.



Features

- Para-Aramid ANSI A7 and Level 4 Puncture and Level 4 Abrasion protection
 - Para-Aramid lining on the fingers, palm and back of hand for complete protection
 - Rough side out double palm for longer life and better gripping power
 - Reinforced thumb to protect severe stress areas
 - Offers that great TrueFit feel you expect from Tillman
 - High-Vis color keeps hands seen and safe
 - Soft, abrasion resistant Goatskin
 - An elastic cuff with a Thermoplastic Rubber (TPR) and hook and loop closure provides a secure fit
 - Breathable form fitting spandex back keeps hands cool and provides a precision fit
- Double stitching on forefinger provides extra strength
Offered in sizes S, M, L, XL, 2X, 3X



Technical Specifications


- Glove Material:** Top grain Goatskin and Spandex back
Cut Resistance: Para-Aramid lining
Reinforcement: Reverse Goatskin
Stitching: Cotton, double stitched reinforcement
Closure: Elastic and Hook & Loop

Applications

- Construction sites
- Wind energy
- Demolition & salvage
- Airports
- Warehouse work
- Road construction
- Farming & Agriculture
- Shipyards
- Utility crews
- Railway and metro workers

Packaging Information

Size	SKU	Piece Information					Inner Pack Info - 12 Pcs					Master Pack Info - 72 Pcs				
		Piece UPC	L	W	H	Wt	Inner Pk UPC	L	W	H	Wt	Master Pk UPC	L	W	H	Wt
Small	1477S	608134147723	9	4	.48"		NA	9	4	5.75"	3.2 lbs	NA	16"	12.5"	16"	19.20 lbs
Medium	1477M	608134147716	9.25	4.25	.50"		NA	9.25	4.25	6.0"	3.4 lbs	NA	16"	12.5"	16"	20.40 lbs
Large	1477L	608134147709	9.5	4.5	.54"		NA	9.5	4.5	6.5"	3.6 lbs	NA	16"	12.5"	16"	21.60 lbs
X Large	1477XL	608134147747	9.75	4.75	.58"		NA	9.75	4.75	7.0"	3.8 lbs	NA	16"	12.5"	16"	22.80 lbs
2X Large	14772X	608134147754	10	5	.61"		NA	10	5	7.5"	4.0 lbs	NA	16"	12.5"	16"	24.00lbs
3X Large	14773X	608134147761	10.3	5.25	.63"		NA	10.3	5.25	7.8"	4.2 lbs	NA	16"	12.5"	16"	25.20 lbs



TILLMAN®

The Brand Pros Demand



TILLMAN®

1477 TrueFit™ Goatskin Gloves With ANSI A& Cut Resistance

DECLARATION OF CONFORMITY

Tillman TrueFit 1477 Handling Gloves, PN 1477 ANSI Declaration of Conformity

Manufacturer

John Tillman Company
1300 W Artesia Blvd
Compton, CA. 90220
USA

Product

Part Number: 1477 Sizes: S, M, L, XL, 2X, 3X

Declaration

John Tillman Company declares that the Model 1477 glove is in conformity with the provisions of the American National Standard for Hand Protection, ANSI ISEA 105-2016.



Testing Laboratory

TRI Environmental
9063 Bee Cave Road
Austin TX. 78733
USA

Performance Data

ANSI - 105 (2016)

Cut Resistance - A7

Interpolated Weight (g) to Cut after 0.8 in (20 mm) of Blade Travel -- 4524

Abrasion Resistance - 4

Average Initial Weight - Zero Cycle (Gram)	9.5622
Number of Cycle require to give Specific Destruction	5186
Average Weight - at the end of test (Gram)	8.34895
Percent Change in Weight at end of test (%)	12.602

Puncture Resistance - 4

	Thickness (0.001)	Force (0.1 lbs)	Force (N)	Deflection (0.1 In)
Average	0.133	40.4	179.77	0.31
Minimum	0.121	31.49	140.13	0.22
Std. Dev.	0.008	6.06	36.97	0.07




Authorized Signature

Name: Jeffrey S Shipley
Title of Signatory: Director of Marketing and Product Development
Date: March

Signature:

May 19, 2020

Date:



TILLMAN®

The Brand Pros Demand