



### SPECIFICATION SHEET

#### Description

The Tillman lightweight flame resistant cotton welding bib is designed to self-extinguish when exposed to flame or thermal ignition sources. This bib with a snap closure attaches to the 6221 cape sleeve and provides resistance against sparks, spatter and accidental flame.

#### Features

- Offered in sizes S-XL, 2X, 3X, 4X
- Made from flame resistant, 100% cotton Westex® FR7A®
- 9 oz flame resistant 100% cotton fabric meets ASTM D6413-10
- ASTM D6413-10 is used to determine a pass/fail criteria for ASTM F1506, which requires a maximum char length of 6 inches
- Rugged snap closure
- Made to attached to the Tillman 6221 cape sleeve
- Maintains flame resistance for up to 50 home washings at 145°F or 25 commercial washings up to 165°F
- Offers protection from sudden flame exposure, welding sparks and spatter



#### Technical Specifications

<b>Jacket Material:</b>	9 oz Westex FR-7A Flame Resistant Cotton
<b>Jacket Color:</b>	Green
<b>Closure:</b>	Snaps
<b>Flame Resistance:</b>	ASTM D 6413-10
<b>Arc Rating</b>	NA
<b>Reflectivity:</b>	NA

#### Applications

- Construction sites
- Wind energy
- Demolition & salvage
- Steel Mills
- Manufacturing
- Road construction
- Farming & Agriculture
- Shipyards
- TIG Welding
- MIG Welding

#### Packaging Information

Size	SKU	Piece Information			Wt
		Piece UPC	Chest (")	L (")	
Small-X Large	6120	608134612009	NA	NA	
2X Large	61202X	608134612054	NA	NA	
3X Large	61203X	608134612061	NA	NA	
4X Large	61204X	608134612078	NA	NA	

John Tillman Co., Compton, CA 90220 • P: (800) 255-5480 • F: (310) 764-0104 • jtillman.com • info@jtillman.com

Warning — Gloves are cut-resistant, not cut proof. Extreme caution should be used when handling sharp objects and around machinery. Read, understand and use. Inspect gloves before each use and remove from service if there is any evidence of damage or excessive wear.

